

View Online at <https://aerobasegroup.com/nsn/5930-00-001-5887>

Thread Class:

2a

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Weatherproof

Bushing Length:

Between 0.969 inches and 1.031 inches

Body Length:

1.200 inches

Body Width:

1.000 inches

Body Height:

1.000 inches

Actuator Style:

Roller plunger

Actuator Free Position Height:

0.700 inches

Actuator Roller Diameter:

0.375 inches

Actuator Roller Width:

0.120 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

4 pole, double throw, one position momentary single switch unit

Switch Release Force:

160.0 ounces

Switch Actuating Force:

180.0 ounces

Actuator Movement:

0.180 pretravel inches and 0.200 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 3.000 amperes inductive dc and 2.000 amperes lamp dc and 5.000 amperes resistive ac and 3.000 amperes inductive ac and 2.000 amperes lamp ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

12 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0