

View Online at <https://aerobasegroup.com/nsn/5930-00-001-5887>

**Thread Class:**

2a

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Weatherproof

**Bushing Length:**

Between 0.969 inches and 1.031 inches

**Body Length:**

1.200 inches

**Body Width:**

1.000 inches

**Body Height:**

1.000 inches

**Actuator Style:**

Roller plunger

**Actuator Free Position Height:**

0.700 inches

**Actuator Roller Diameter:**

0.375 inches

**Actuator Roller Width:**

0.120 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

4 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

160.0 ounces

**Switch Actuating Force:**

180.0 ounces

**Actuator Movement:**

0.180 pretravel inches and 0.200 overtravel inches and 0.020 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 3.000 amperes inductive dc and 2.000 amperes lamp dc and 5.000 amperes resistive ac and 3.000 amperes inductive ac and 2.000 amperes lamp ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

12 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0