

View Online at <https://aerobasegroup.com/nsn/5930-00-001-7260>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Weatherproof

Overall Length:

1.346 inches

Overall Height:

2.418 inches

Overall Width:

1.680 inches

Bushing Length:

0.469 inches

Body Length:

1.346 inches

Body Width:

1.686 inches

Case Material:

Metal

Actuator Style:

Round

Actuator Diameter:

Between 0.420 inches and 0.432 inches

Actuator Height:

Between 0.874 inches and 0.968 inches

Actuator Position-action Relationship:

Down position momentary and center position maintained

Actuator Position-locking Relationship:

Down position no locking action and center position locked in

Maximum Voltage Rating In Volts:

250.0 ac and 250.0 dc

Mounting Surface To Terminal End Distance:

1.328 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

4 pole, single throw, normally open, momentary action single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive ac and 7.000 amperes inductive ac and 500.0 milliamperes resistive dc

Test Data Document:

81349-mil-s-8834 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

8 tab w/screw

Specification Data:

96906-ms24614 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0