

View Online at <https://aerobasegroup.com/nsn/5930-00-001-7263>

Thread Class:

2b single pressure connection

Inside Diameter:

0.438 inches single connection

Thread Length:

0.562 inches single pressure connection

Hazardous Locations/environmental Protection:

Corrosion resistant

Overall Length:

2.875 inches

Overall Height:

3.187 inches

Overall Width:

3.688 inches

Body Length:

2.312 inches

Body Height:

2.312 inches

Pressure Switch Type:

Gage

Mounting Method:

Flush

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Thread Size:

0.438 inches single pressure connection

Nonpile-up Contact Arrangement:

2 pole, single throw, normally closed, double break, momentary action

Terminal Type:

Screw

Contact Load Current Rating:

8.0 amperes resistive load first voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+30.00 to 80.00 actuation point pounds per square inch gage and +17.00/+63.00 deactuation point pounds per square inch gage

Contact Adjustment Type:

Internal deactuation point hex nut and internal actuation point hex nut

Contact Voltage Rating In Volts:

600.0 dc at sea level third voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Gas or liquid

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Style Designator:

Rectangular

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0