## NSN 5930-00-001-7263

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-001-7263

View Online at https://aerobasegroup.com/nsn/5930-00-001-7263
Thread Class:
2b single pressure connection
Inside Diameter:
0.438 inches single connection
Thread Length:
0.562 inches single pressure connection
Hazardous Locations/environmental Protection:
Corrosion resistant
Overall Length:
2.875 inches
Overall Height:
3.187 inches
Overall Width:
3.688 inches
Body Length:
2.312 inches
Body Height:
2.312 inches
Pressure Switch Type:
Gage
Mounting Method:
Flush
Features Provided:
Electrical access port
Contact Action Stimulus:
Increase
Thread Size:
0.438 inches single pressure connection
Nonpile-up Contact Arrangement:
2 pole, single throw, normally closed, double break, momentary action
Terminal Type:
Screw
Contact Load Current Rating:
8.0 amperes resistive load first voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+30.00 to 80.00 actuation point pounds per square inch gage and +17.00/+63.00 deactuation point pounds per square inch gage
Contact Adjustment Type:
Internal deactuation point hex nut and internal actuation point hex nut

Contact Voltage Rating In Volts:

600.0 dc at sea level third voltage

## NSN 5930-00-001-7263

Pressure Switch - Page 2 of 2



Pressure Connector Type:
Plain, threaded internal single connection
Media For Which Designed:
Gas or liquid
Precious Material And Location:
Contact surfaces silver
Precious Material:
Silver
Style Designator:
Rectangular
Thread Series Designator:
Unf single pressure connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0