# NSN 5930-00-001-7263

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-001-7263

## **Thread Class:**

2b single pressure connection

#### **Inside Diameter:**

0.438 inches single connection

## **Thread Length:**

0.562 inches single pressure connection

## Hazardous Locations/environmental Protection:

Corrosion resistant

#### **Overall Length:**

2.875 inches

#### **Overall Height:**

3.187 inches

#### **Overall Width:**

3.688 inches

#### Body Length:

2.312 inches

## Body Height:

2.312 inches

#### 2.512 1101165

Pressure Switch Type:

Gage

## Mounting Method:

Flush

## **Features Provided:**

Electrical access port

## **Contact Action Stimulus:**

Increase

## Thread Size:

0.438 inches single pressure connection

## Nonpile-up Contact Arrangement:

2 pole, single throw, normally closed, double break, momentary action

#### Terminal Type:

Screw

## **Contact Load Current Rating:**

8.0 amperes resistive load first voltage

## **Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

## Contact Adjustment Range:

+30.00 to 80.00 actuation point pounds per square inch gage and +17.00/+63.00 deactuation point pounds per square inch gage

#### **Contact Adjustment Type:**

Internal deactuation point hex nut and internal actuation point hex nut

## **Contact Voltage Rating In Volts:**

600.0 dc at sea level third voltage

## NSN 5930-00-001-7263

Pressure Switch - Page 2 of 2



Pressure Connector Type:

Plain, threaded internal single connection

## Media For Which Designed:

Gas or liquid

## **Precious Material And Location:**

Contact surfaces silver

## **Precious Material:**

Silver

Style Designator:

Rectangular

## **Thread Series Designator:**

Unf single pressure connection

Shelf Life:

N/a

#### Unit Of Measure:

---

## Demilitarization:

No

## Fiig:

A048b0