

View Online at <https://aerobasegroup.com/nsn/5930-00-001-7479>

Thread Class:

2b single pressure connection

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

4.938 inches

Overall Height:

5.125 inches

Overall Width:

2.875 inches

Body Height:

2.750 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Longest Horizontal Distance Between Mounting Centers:

2.406 inches

Shortest Horizontal Distance Between Mounting Centers:

0.656 inches

Longest Vertical Distance Between Mounting Centers:

3.281 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

20 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

160.00 pounds per square inch gage

Thread Size:

0.4375 inches single pressure connection

Mounting Facility Pattern:

Isosceles triangle

Terminal Type:

Screw

Contact Load Current Rating:

9.6 amperes resistive load fourth voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+15.00/+50.00 actuation point pounds per square inch gage and +11.00 to 46.00 deactuation point pounds per square inch gage

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Stimulus Rating:

4.00 differential point pounds per square inch gage

Contact Voltage Rating In Volts:

550.0 dc at sea level third voltage

Pressure Connector Type:

Plain, threaded internal single connection

Special Features:

Alarm system

Media For Which Designed:

Gas or liquid

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Rectangular w/bracket

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0