

View Online at <https://aerobasegroup.com/nsn/5930-00-003-5405>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Vibration resistant

Overall Length:

0.750 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.250 inches

Overall Height:

0.775 inches

Overall Width:

0.345 inches

Body Length:

0.750 inches

Body Width:

0.345 inches

Body Height:

0.516 inches

Unthreaded Mounting Hole Diameter:

0.089 inches

Actuator Style:

Round

Actuator Height:

0.085 inches

Actuator Free Position Height:

0.431 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Hermetically sealed

Mounting Method:

Unthreaded hole

Features Provided:

Actuator seal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

6.0 ounces

Switch Actuating Force:

22.0 ounces

Actuator Movement:

Between 0.011 pretravel inches and 0.007 overtravel inches and 0.001 differential inches and 0.005 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 3.000 amperes motor dc and 5.000 amperes resistive ac and 3.000 amperes inductive ac and 3.000 amperes motor ac

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0