

View Online at <https://aerobasegroup.com/nsn/5930-00-003-5767>

**Body Style:**

Bushing mounted

**Body Diameter:**

Between 0.610 inches and 0.640 inches

**Bushing Length:**

0.310 inches

**Body Length:**

1.000 inches

**Actuator Diameter:**

0.500 inches

**Actuator Height:**

0.770 inches

**Actuator Color:**

White single actuator

**Illuminated Actuator Color:**

Green single actuator

**Maximum Voltage Rating In Volts:**

125.0 ac and 30.0 dc

**Inclosure Type:**

Fully enclosed

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

4 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

3.000 amperes resistive dc and 2.000 amperes inductive dc and 3.000 amperes resistive ac and 2.000 amperes inductive ac

**Test Data Document:**

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

14 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0