

View Online at <https://aerobasegroup.com/nsn/5930-00-003-5803>

Thread Class:

3a single pressure connection

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

4.000 inches

Outside Diameter:

0.875 inches single connection

Overall Height:

1.500 inches

Overall Width:

1.500 inches

Body Length:

2.648 inches

Overall Diameter:

0.850 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 275.0 degrees fahrenheit

Mounting Method:

Input port

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Increase

Proof Pressure:

4500.00 pounds per square inch

Thread Size:

0.875 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Sensing Element Burst Pressure:

7500.00 pounds per square inch

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

5.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

700.00 actuation point pounds per square inch gage and 900.00 actuation point pounds per square inch gage and 400.00 deactuation point pounds per square inch gage and 600.00 deactuation point pounds per square inch gage

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Plain, threaded external single connection

Media For Which Designed:

Liquid

Style Designator:

Rectangular

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0