

View Online at <https://aerobasegroup.com/nsn/5930-00-003-6643>

Thread Class:

3a single pressure connection

Overall Length:

3.100 inches

Outside Diameter:

0.438 inches single connection

Body Length:

2.000 inches

Overall Diameter:

0.870 inches

Pressure Switch Type:

Gage

Width Across Flats:

0.750 inches

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 230.0 degrees fahrenheit

Mounting Method:

Terminal, wire-lead

Contact Action Stimulus:

Increase

Proof Pressure:

350.00 pounds per square inch

Thread Size:

0.438 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Sensing Element Burst Pressure:

300.00 pounds per square inch gage

Terminal Type:

Wire lead

Contact Load Current Rating:

250.0 milliamperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

55.00 actuation point pounds per square inch gage and 65.00 actuation point pounds per square inch gage and 50.00 deactuation point pounds per square inch and 5.00 actuation point pounds per square inch gage

Contact Voltage Rating In Volts:

29.0 dc at sea level single voltage

Pressure Connector Type:

Flared, threaded external single connection

Media For Which Designed:

Liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0