## NSN 5930-00-003-7706

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-003-7706

**Thread Class:** 

2a single mounting facility

Thread Length:

0.410 inches single mounting facility

**Hazardous Locations/environmental Protection:** 

Explosion proof

**Overall Length:** 

4.914 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.208 inches single actuator and 0.212 inches single actuator

**Shaft Diameter:** 

0.248 inches single actuator and 0.252 inches single actuator

**Shaft Length:** 

0.780 inches single actuator

**Overall Diameter:** 

1.172 inches

**Individual Section Quantity:** 

10

**Nonturn Device Type:** 

Slotted bushing at 12: 00 o'clock

**Operating Tempurature Range:** 

-65.0 to 125.0 degrees celsius

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

Pole Quantity:

1 each section front

**Throw Quantity:** 

12 each section rear

**Mounting Method:** 

Threaded bushing single mounting facility

**Thread Size:** 

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:** 

28.0 dc at sea level

**Shaft Flat/slot Angular Location:** 

180.0 degrees from contact position 1 single actuator

**Rotor Through Connection Quantity:** 

1 each section

**Switch Actuator Indexing Position Quantity:** 

12 single actuator

## **NSN 5930-00-003-7706**Rotary Switch - Page 2 of 2

A052b0



Shaft Type:
Round, flatted single actuator
Terminal Type:
Tab, solder lug
Contact Switching Action:
Breaks before makes each section rear
Switch Actuator Positioning Increment:
30.0 degrees single actuator
Contact Load Current Rating:
1.0 amperes resistive load dc at sea level and 500.0 milliamperes inductive load dc at sea level
Style Designator:
Tap, circular, bushing mount
Test Data Document:
81349-mil-s-3786/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef single mounting facility
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiia: