

View Online at <https://aerobasegroup.com/nsn/5930-00-003-7724>

**Thread Class:**

2a

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Watertight

**Body Diameter:**

0.750 inches

**Bushing Length:**

0.410 inches

**Body Length:**

0.947 inches

**Actuator Diameter:**

0.750 inches

**Actuator Height:**

0.870 inches

**Actuator Color:**

Red single actuator

**Illuminated Actuator Color:**

Red single actuator

**Maximum Voltage Rating In Volts:**

125.0 ac and 30.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.563 inches

**Nonpile-up Contact Arrangement:**

3 two circuit, double break/double make, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

2.000 amperes resistive dc and 500.000 milliamperes resistive dc and 2.000 amperes resistive ac and 500.000 milliamperes inductive ac

**Thread Series Designator:**

Un

**Terminal Type And Quantity:**

14 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0