NSN 5930-00-003-7724

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-003-7724 **Thread Class:** 2a **Body Style: Bushing mounted Hazardous Locations/environmental Protection:** Watertight **Body Diameter:** 0.750 inches **Bushing Length:** 0.410 inches **Body Length:** 0.947 inches **Actuator Diameter:** 0.750 inches **Actuator Height:** 0.870 inches **Actuator Color:** Red single actuator **Illuminated Actuator Color:** Red single actuator **Maximum Voltage Rating In Volts:** 125.0 ac and 30.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded bushing **Features Provided:** Actuator seal Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.563 inches **Nonpile-up Contact Arrangement:** 3 two circuit, double break/double make, one position momentary single switch unit **Contact Load Current Rating At Maximum Rated Voltage:** 2.000 amperes resistive dc and 500.000 milliamperes resistive dc and 2.000 amperes resistive ac and 500.000 milliamperes inductive ac **Thread Series Designator:** Un **Terminal Type And Quantity:**

N/a

Shelf Life:

14 tab, solder lug

NSN 5930-00-003-7724

Push Switch - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A053a0