NSN 5930-00-004-0051

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-004-0051

| Thread Class: |
|---|
| 3b single pressure connection |
| Inside Diameter: |
| 0.438 inches single connection |
| Overall Length: |
| 3.250 inches |
| Body Diameter: |
| 1.380 inches |
| Body Length: |
| 2.170 inches |
| Overall Diameter: |
| 1.380 inches |
| Pressure Switch Type: |
| Gage |
| Operating Tempurature Rating: |
| Between -65.0 degrees fahrenheit and 165.0 degrees fahrenheit |
| Mounting Method: |
| Clamp |
| Features Provided: |
| Electrical box connector |
| Thready Qty Per Inch (tpi): |
| 20 single pressure connection |
| Contact Action Stimulus: |
| Increase |
| Proof Pressure: |
| 4500.00 pounds per square inch |
| Thread Size: |
| 0.438 inches single pressure connection |
| Nonpile-up Contact Arrangement: |
| 1 pole, double throw, one position momentary |
| Terminal Type: |
| Connector, receptacle |
| Contact Load Current Rating: |
| 5.0 amperes resistive load second voltage and 2.5 amperes inductive load second voltage |
| Contact Adjustability: |
| Deactuation point adjustable and actuation point adjustable |
| Contact Adjustment Range: |
| +800.00 to 2000.00 actuation point pounds per square inch gage and +550.00 to 1750.00 deactuation point pounds per square inch gage |
| Contact Adjustment Type: |
| External deactuation point screw and external actuation point screw |

Contact Stimulus Rating:

250.00 differential point pounds per square inch gage

NSN 5930-00-004-0051

Pressure Switch - Page 2 of 2



Contact Voltage Rating In Volts: 30.0 dc at sea level second voltage **Pressure Connector Type:** Plain, threaded internal single connection Frequency In Hertz: 60.0 single voltage Media For Which Designed: Liquid Style Designator: Cylindrical **Thread Series Designator:** Unf single pressure connection Shelf Life: N/a **Unit Of Measure:** Demilitarization:

No Fiig: A048b0