

View Online at <https://aerobasegroup.com/nsn/5930-00-004-0051>

Thread Class:

3b single pressure connection

Inside Diameter:

0.438 inches single connection

Overall Length:

3.250 inches

Body Diameter:

1.380 inches

Body Length:

2.170 inches

Overall Diameter:

1.380 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 165.0 degrees fahrenheit

Mounting Method:

Clamp

Features Provided:

Electrical box connector

Thready Qty Per Inch (tpi):

20 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

4500.00 pounds per square inch

Thread Size:

0.438 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

5.0 amperes resistive load second voltage and 2.5 amperes inductive load second voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+800.00 to 2000.00 actuation point pounds per square inch gage and +550.00 to 1750.00 deactuation point pounds per square inch gage

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Stimulus Rating:

250.00 differential point pounds per square inch gage

Contact Voltage Rating In Volts:

30.0 dc at sea level second voltage

Pressure Connector Type:

Plain, threaded internal single connection

Frequency In Hertz:

60.0 single voltage

Media For Which Designed:

Liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0