## NSN 5930-00-004-0051

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-004-0051

Thread Class:
3b single pressure connection
Inside Diameter:
0.438 inches single connection
Overall Length:
3.250 inches
Body Diameter:
1.380 inches
Body Length:
2.170 inches
Overall Diameter:
1.380 inches
Pressure Switch Type:
Gage
Operating Tempurature Rating:
Between -65.0 degrees fahrenheit and 165.0 degrees fahrenheit
Mounting Method:
Clamp
Features Provided:
Electrical box connector
Thready Qty Per Inch (tpi):
20 single pressure connection
Contact Action Stimulus:
Increase
Proof Pressure:
4500.00 pounds per square inch
Thread Size:
0.438 inches single pressure connection
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Connector, receptacle
Contact Load Current Rating:
5.0 amperes resistive load second voltage and 2.5 amperes inductive load second voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+800.00 to 2000.00 actuation point pounds per square inch gage and +550.00 to 1750.00 deactuation point pounds per square inch gage
Contact Adjustment Type:
External deactuation point screw and external actuation point screw

## **Contact Stimulus Rating:**

250.00 differential point pounds per square inch gage

## NSN 5930-00-004-0051

Pressure Switch - Page 2 of 2



## **Contact Voltage Rating In Volts:** 30.0 dc at sea level second voltage **Pressure Connector Type:** Plain, threaded internal single connection Frequency In Hertz: 60.0 single voltage Media For Which Designed: Liquid Style Designator: Cylindrical **Thread Series Designator:** Unf single pressure connection Shelf Life: N/a **Unit Of Measure:** Demilitarization:

No Fiig: A048b0