

View Online at <https://aerobasegroup.com/nsn/5930-00-004-1470>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Length:**

Between 0.771 inches and 0.791 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.375 inches

**Overall Height:**

0.795 inches

**Overall Width:**

Between 0.240 inches and 0.260 inches

**Body Length:**

Between 0.771 inches and 0.791 inches

**Body Width:**

Between 0.240 inches and 0.260 inches

**Body Height:**

Between 0.346 inches and 0.366 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

Between 0.087 inches and 0.090 inches

**Actuator Style:**

Leaf

**Actuator Width:**

Between 0.145 inches and 0.175 inches

**Actuator Free Position Height:**

0.598 inches

**Maximum Voltage Rating In Volts:**

30.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

2.0 ounces

**Switch Actuating Force:**

7.0 ounces

**Actuator Movement:**

Between 0.218 pretravel inches and 0.030 overtravel inches and 0.030 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc

**Precious Material And Location:**

Terminal surfaces gold

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A053a0