# NSN 5930-00-004-2103

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-004-2103

## **Thread Class:**

2a single mounting facility

## Thread Length:

0.375 inches single mounting facility

## **Overall Length:**

1.437 inches

#### **Overall Height:**

1.484 inches

#### **Overall Width:**

1.312 inches

#### Shaft Diameter:

0.248 inches single actuator and 0.251 inches single actuator

## Shaft Length:

0.680 inches single actuator

#### **Nonturn Device Radius:**

## 0.438 inches at 3: 00 o'clock

#### Individual Section Quantity:

1

#### Nonturn Device Type:

Tab at 3: 00 o'clock

## Switch Contact Basic Design:

Nonpile-up symmetrical

## **Pole Quantity:**

2 single section rear

#### **Throw Quantity:**

3 single section rear

#### **Mounting Method:**

Threaded bushing single mounting facility

#### Thread Size:

0.375 inches single mounting facility

#### Contact Voltage Rating In Volts:

28.0 dc at sea level

#### Switch Actuator Indexing Position Quantity:

3 single actuator

#### Shaft Type:

Round single actuator

#### **Terminal Type:**

Tab, solder lug

#### **Contact Switching Action:**

Breaks before makes single section rear

# Switch Actuator Positioning Increment:

30.0 degrees single actuator

# NSN 5930-00-004-2103

Rotary Switch - Page 2 of 2



Switch Actuator Stop Device Type: Fixed stop single actuator **Contact Load Current Rating:** 1.5 amperes resistive load dc at sea level Style Designator: Circular wafer, bushing mount **Thread Series Designator:** Unef single mounting facility Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A052b0