# NSN 5930-00-004-2104

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-004-2104

## **Thread Class:**

2a single mounting facility

# Thread Length:

0.375 inches single mounting facility

# **Overall Length:**

1.937 inches

### **Overall Height:**

1.484 inches

#### **Overall Width:**

1.312 inches

#### Shaft Diameter:

0.248 inches single actuator and 0.251 inches single actuator

#### Shaft Length:

0.680 inches single actuator

#### **Nonturn Device Radius:**

# 0.438 inches at 3: 00 o'clock

# Individual Section Quantity:

2

#### Nonturn Device Type:

Tab at 3: 00 o'clock

# Switch Contact Basic Design:

Nonpile-up symmetrical

#### **Pole Quantity:**

1 each section rear

#### **Throw Quantity:**

12 each section rear

## **Mounting Method:**

Threaded bushing single mounting facility

## **Thread Size:**

0.375 inches single mounting facility

## Contact Voltage Rating In Volts:

28.0 dc at sea level

## Switch Actuator Indexing Position Quantity:

12 single actuator

# Shaft Type:

Round single actuator

## **Terminal Type:**

Tab, solder lug

## **Contact Switching Action:**

Breaks before makes each section rear

## Switch Actuator Positioning Increment:

30.0 degrees single actuator

# NSN 5930-00-004-2104

Rotary Switch - Page 2 of 2



**Contact Load Current Rating:** 

1.5 amperes resistive load dc at sea level

Style Designator:

Circular wafer, bushing mount

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A052b0