NSN 5930-00-004-3909

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-004-3909

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Oiltight
Overall Length:
4.000 inches
Overall Height:
2.281 inches
Overall Width:
1.562 inches
Actuator Style:
Round
Actuator Height:
0.625 inches
Actuator Free Position Height:
1.500 inches
Housing Height:
1.875 inches
Housing Length:
4.000 inches
Housing Width:
1.562 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
2.344 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
1.156 inches
Maximum Voltage Rating In Volts:
600.0 ac and 240.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
1 two circuit, double break/double make, one position momentary single switch unit
Switch Actuating Force:
24.0 inch-ounces
Actuator Movement:
10.0 pretravel degrees and 80.0 overtravel degrees and 4.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage: 250.000 milliamperes resistive dc and 1.200 amperes resistive ac

NSN 5930-00-004-3909

Sensitive Switch - Page 2 of 2



Terminal	Type	And	Quantity:
----------	------	-----	-----------

4 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0