

View Online at <https://aerobasegroup.com/nsn/5930-00-004-4330>

**Thread Class:**

2a

**Body Style:**

Bushing mount

**Bushing Length:**

Between 0.448 inches and 0.488 inches

**Body Length:**

Between 0.786 inches and 0.866 inches

**Body Width:**

Between 0.452 inches and 0.532 inches

**Body Height:**

0.600 inches

**Switch Actuator Quantity:**

1

**Actuator Style:**

Round

**Actuator Diameter:**

0.236 inches

**Actuator Height:**

Between 0.373 inches and 0.453 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained and center position maintained

**Maximum Voltage Rating In Volts:**

30.0 dc

**Mounting Surface To Terminal End Distance:**

0.700 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

4 pole, double throw, three positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

4.000 amperes resistive dc

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

12 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0