

View Online at <https://aerobasegroup.com/nsn/5930-00-004-5906>

Overall Length:

1.177 inches

Overall Height:

0.805 inches

Body Diameter:

0.605 inches

Body Height:

0.455 inches

Distance Between Mounting Facility Centers:

0.932 inches

Tempurature Sensing Element Type:

Disc

Mounting Method:

Bracket

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

3.0 amperes resistive load first voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

190.00 actuation point degrees fahrenheit and 200.00 actuation point degrees fahrenheit and 178.00 deactuation point degrees fahrenheit and 188.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

30.0 dc at sea level second voltage

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Gas

Style Designator:

Disc w/flange

Test Data Document:

96906-mil-std-202 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0