

View Online at <https://aerobasegroup.com/nsn/5930-00-004-6184>

Thread Class:

2a all threaded stud

Thread Length:

0.187 inches all threaded stud

Overall Height:

Between 0.564 inches and 0.654 inches

Body Height:

Between 0.232 inches and 0.266 inches

Overall Diameter:

Between 0.182 inches and 0.196 inches

Temperature Sensing Element Type:

Disc

Mounting Method:

Threaded stud

Features Provided:

Hermetically sealed case and internally grounded

Thready Qty Per Inch (tpi):

40 all threaded stud

Contact Action Stimulus:

Increase

Thread Size:

0.112 inches all threaded stud

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

1.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

222.00 actuation point degrees fahrenheit and 238.00 actuation point degrees fahrenheit and 192.00 deactuation point degrees fahrenheit and 208.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

30.0 dc at sea level second voltage

Frequency In Hertz:

60.0 single voltage

Media For Which Designed:

Gas

Style Designator:

Disc

Test Data Document:

96906-mil-std-202 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical" "average" "" etc.)

Thread Series Designator:

Unc all threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0