

View Online at <https://aerobasegroup.com/nsn/5930-00-004-6210>

Thread Class:

3a single pressure connection

Overall Length:

1.549 inches

Outside Diameter:

0.375 inches single connection

Body Length:

1.000 inches

Overall Diameter:

1.230 inches

Pressure Switch Type:

Absolute

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 275.0 degrees fahrenheit

Mounting Method:

Inlet connection

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Increase

Proof Pressure:

60.00 pounds per square inch

Thread Size:

0.375 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Turret

Contact Load Current Rating:

3.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

26.00 actuation point pounds per square inch absolute and 29.00 actuation point pounds per square inch absolute and 22.00 deactuation point pounds per square inch absolute and 26.00 deactuation point pounds per square inch absolute and 3.00 differential point pounds per square inch absolute

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Flared, threaded external single connection

Media For Which Designed:

Gas

Style Designator:

Cylindrical

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0