

View Online at <https://aerobasegroup.com/nsn/5930-00-004-7712>

Thread Length:

0.875 inches single pressure connection

Overall Length:

4.750 inches

Overall Height:

5.550 inches

Overall Width:

3.000 inches

Body Height:

2.625 inches

Unthreaded Mounting Hole Diameter:

0.250 inches

Distance Between Mounting Facility Centers:

2.625 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

27 single pressure connection

Contact Action Stimulus:

Increase

Thread Size:

0.875 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Sensing Element Burst Pressure:

200.00 pounds per square inch

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

3.2 amperes resistive load first voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Type:

External deactuation point knob and external actuation point screw

Contact Stimulus Rating:

9.00 differential point pounds per square inch and 15.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

550.0 ac at sea level first voltage

Pressure Connector Type:

Plain, threaded internal single connection

Frequency In Hertz:

60.0 second voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular w/bracket

Thread Series Designator:

Uns single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0