NSN 5930-00-004-7712



| Pressure Switch - Page 1 of 2 | U |
|---|---|
| View Online at https://aerobasegroup.com/nsn/5930-00-004-7712 | |
| Thread Length: | |
| 0.875 inches single pressure connection | |
| Overall Length: | |
| 4.750 inches | |
| Overall Height: | |
| 5.550 inches | |
| Overall Width: | |
| 3.000 inches | |
| Body Height: | |
| 2.625 inches | |
| Unthreaded Mounting Hole Diameter: | |
| 0.250 inches | |
| Distance Between Mounting Facility Centers: | |
| 2.625 inches | |
| Pressure Switch Type: | |
| Gage | |
| Mounting Method: | |
| Bracket and unthreaded hole | |
| Features Provided: | |
| Electrical access port | |
| Thready Qty Per Inch (tpi): | |
| 27 single pressure connection | |
| Contact Action Stimulus: | |
| Increase | |
| Thread Size: | |
| | |

0.875 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Sensing Element Burst Pressure:

200.00 pounds per square inch

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

3.2 amperes resistive load first voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Type:

External deactuation point knob and external actuation point screw

Contact Stimulus Rating:

9.00 differential point pounds per square inch and 15.00 differential point pounds per square inch

NSN 5930-00-004-7712

Pressure Switch - Page 2 of 2



Contact Voltage Rating In Volts: 550.0 ac at sea level first voltage Pressure Connector Type: Plain, threaded internal single connection Frequency In Hertz: 60.0 second voltage Media For Which Designed: Gas or liquid Style Designator: Rectangular w/bracket Thread Series Designator: Uns single pressure connection Shelf Life: N/a Unit Of Measure: ---

Demilitarization:

No Fiig: A048b0