NSN 5930-00-004-7712



Pressure Switch - Page 1 of 2	_
View Online at https://aerobasegroup.com/nsn/5930-00-004-7712	
Thread Length:	
0.875 inches single pressure connection	
Overall Length:	
4.750 inches	
Overall Height:	
5.550 inches	
Overall Width:	
3.000 inches	
Body Height:	
2.625 inches	
Unthreaded Mounting Hole Diameter:	
0.250 inches	
Distance Between Mounting Facility Centers:	
2.625 inches	
Pressure Switch Type:	
Gage	
Mounting Method:	
Bracket and unthreaded hole	
Features Provided:	
Electrical access port	
Thready Qty Per Inch (tpi):	
27 single pressure connection	
Contact Action Stimulus:	
Increase	
Thread Size:	

0.875 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Sensing Element Burst Pressure:

200.00 pounds per square inch

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

3.2 amperes resistive load first voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Type:

External deactuation point knob and external actuation point screw

Contact Stimulus Rating:

9.00 differential point pounds per square inch and 15.00 differential point pounds per square inch

NSN 5930-00-004-7712

Pressure Switch - Page 2 of 2



Contact Voltage Rating In Volts: 550.0 ac at sea level first voltage Pressure Connector Type: Plain, threaded internal single connection Frequency In Hertz: 60.0 second voltage Media For Which Designed: Gas or liquid Style Designator: Rectangular w/bracket Thread Series Designator: Uns single pressure connection Shelf Life: N/a Unit Of Measure: ---

Demilitarization:

No Fiig: A048b0