

View Online at <https://aerobasegroup.com/nsn/5930-00-004-8993>

**Ac Voltage Rating:**

220.0 volts 2nd operating power rqmt

**Dc Voltage Rating:**

6.0 volts 3rd operating power rqmt

**Frequency Rating:**

60.0 hertz

**Overall Diameter:**

1.875 inches

**Actuation Method:**

Buoyancy

**Internal Battery Accommodation:**

Not included

**Current Rating At Maximum Rated Voltage:**

200.0 milliamperes load

**Voltage Rating At Maximum Rated Current:**

50.0 volts

**Float Quantity:**

3

**Operating Temperature Rating:**

Between 0.0 degrees celsius and 85.0 degrees celsius

**Mounting Method:**

Thread

**Mounting Position:**

Vertical

**Maximum Current Rating:**

200.0 milliamperes load

**Contact Arrangement:**

Spst, normally closed, dry

**Relay:**

Not included

**Liquid Type For Which Designed:**

Demineralized water

**Float Effective Travel:**

0.500 inches

**Mounting Dimensions:**

Mtd by 3/8-18 npt thd shaft end

**Tank Insertion Length:**

25.880 inches

**Phase:**

Single/three

**Special Features:**

Three switches, actuated at 23.500 in., 16.880 in., 4.880 in. From top of tank

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T109-d