## NSN 5930-00-004-8993

Liquid Level Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-004-8993

Ac Voltage Rating:
220.0 volts 2nd operating power rqmt
Dc Voltage Rating:
6.0 volts 3rd operating power rqmt
Frequency Rating:
60.0 hertz
Overall Diameter:
1.875 inches
Actuation Method:
Buoyancy
Internal Battery Accommodation:
Not included
Current Rating At Maximum Rated Voltage:
200.0 milliamperes load
Voltage Rating At Maximum Rated Current:
50.0 volts
Float Quantity:
3
Operating Tempurature Rating:
Between 0.0 degrees celsius and 85.0 degrees celsius
Mounting Method:
Thread
Mounting Position:
Vertical
Maximum Current Rating:
200.0 milliamperes load
Contact Arrangement:
Spst, normally closed, dry
Relay:
Not included
Liquid Type For Which Designed:
Demineralized water
Float Effective Travel:
0.500 inches
Mounting Dimensions:
Mtd by 3/8-18 npt thd shaft end
Tank Insertion Length:
25.880 inches
Phase:
Single/three
Special Features:
Three switches, actuated at23.500 in., 16.880 in., 4.880 in. From top of tank

## **NSN 5930-00-004-8993** Liquid Level Switch - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

T109-d