NSN 5930-00-005-0362

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-005-0362

Thread Class:

2a single mounting facility

Thread Length:

0.312 inches single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

1.915 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.094 inches single actuator

Shaft Diameter:

0.125 inches single actuator

Shaft Length:

0.375 inches single actuator

Overall Diameter:

0.781 inches

Nonturn Device Radius:

0.260 inches at 3: 00 o'clock

Individual Section Quantity:

2

Nonturn Device Type:

Tab at 3: 00 o'clock

Operating Tempurature Range:

-65.0 to 85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

3 1st section front

Throw Quantity:

4 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Momentary Position:

Counterclockwise single actuator

Rotor Through Connection Quantity:

3 1st section

NSN 5930-00-005-0362

Rotary Switch - Page 2 of 2



Switch Actuator Indexing Position Quantity: 4 single actuator Shaft Type: Round, flatted single actuator **Terminal Type:** Tab, solder lug **Contact Switching Action:** Breaks before makes each section rear **Switch Actuator Positioning Increment:** 30.0 degrees single actuator **Detent Rotational Torque Range:** +0.400/+2.700 inch-pounds single actuator Switch Actuator Stop Device Type: Fixed stop single actuator **Contact Load Current Rating:** 75.0 milliamperes resistive load ac at sea level **Precious Material And Location:** Terminals gold and contact surfaces silver **Precious Material:** Gold and silver Style Designator: Tap, circular, bushing mount **Thread Series Designator:** Unef single mounting facility Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A052b0