

View Online at <https://aerobasegroup.com/nsn/5930-00-005-2984>

Inside Diameter:

0.250 inches single connection

Thread Length:

0.625 inches single pressure connection

Overall Length:

3.375 inches

Overall Height:

4.250 inches

Overall Width:

2.188 inches

Body Height:

3.250 inches

Pressure Switch Type:

Gage

Mounting Method:

Input port

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Thread Size:

0.250 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Screw

Contact Load Current Rating:

8.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+0.50 to 9.00 actuation point pounds per square inch and +0.50/+9.00 deactuation point pounds per square inch

Contact Adjustment Type:

External actuation point pointer with scale and external deactuation point pointer with scale

Contact Stimulus Rating:

1.00 differential point pounds per square inch and 5.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

240.0 ac at sea level first voltage

Pressure Connector Type:

Plain, threaded internal single connection

Frequency In Hertz:

60.0 second voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0