# NSN 5930-00-005-3150

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-005-3150

## **Thread Class:**

2a single mounting facility

## Thread Length:

0.380 inches single mounting facility

# **Overall Length:**

2.310 inches

## **Overall Height:**

1.313 inches

## **Overall Width:**

1.250 inches

## First Flat Length:

0.310 inches single actuator

## Flat Height:

0.216 inches single actuator and 0.220 inches single actuator

## Shaft Diameter:

0.248 inches single actuator and 0.251 inches single actuator

## Shaft Length:

0.810 inches single actuator

## **Nonturn Device Radius:**

0.531 inches at 3: 00 o'clock

# Individual Section Quantity:

2

## Nonturn Device Type:

Tab at 3: 00 o'clock

#### **Operating Tempurature Range:**

-65.0/+85.0 degrees celsius

## Switch Contact Basic Design:

Nonpile-up symmetrical

## **Pole Quantity:**

4 each section rear

#### **Throw Quantity:**

2 each section rear

## **Mounting Method:**

Threaded bushing single mounting facility

#### **Thread Size:**

0.375 inches single mounting facility

# **Contact Voltage Rating In Volts:**

28.0 dc at sea level

# Shaft Flat/slot Angular Location:

330.0 degrees from nonturn device single actuator

# Switch Actuator Indexing Position Quantity:

2 single actuator

# NSN 5930-00-005-3150

Rotary Switch - Page 2 of 2



## Shaft Type:

Round, flatted single actuator

## **Terminal Type:**

Tab, solder lug

## **Contact Switching Action:**

Breaks before makes each section rear

# Switch Actuator Positioning Increment:

30.0 degrees single actuator

## Switch Actuator Stop Device Type:

Fixed stop single actuator

## **Contact Load Current Rating:**

500.0 milliamperes resistive load dc at sea level and 50.0 milliamperes inductive load dc at sea level

#### Style Designator:

Circular wafer, bushing mount

## **Test Data Document:**

81349-mil-s-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Thread Series Designator:**

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

## **Demilitarization:**

No

Fiig:

A052b0