NSN 5930-00-005-7156

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-005-7156

Thread Class:

3b single pressure connection

Inside Diameter:

0.438 inches single connection

Thread Length:

0.568 inches single pressure connection

Overall Length:

3.500 inches

Body Length:

1.768 inches

Overall Diameter:

1.870 inches

Unthreaded Mounting Hole Diameter:

Between 0.193 inches and 0.210 inches

Pressure Switch Type:

Gage

Mounting Facility Circle Radius:

0.697 inches

Operating Tempurature Rating:

Between -65.0 degrees fahrenheit and 300.0 degrees fahrenheit

Mounting Method:

Flange and unthreaded hole

Contact Action Stimulus:

Increase

Proof Pressure:

240.00 pounds per square inch

Thread Size:

0.4375 inches single pressure connection

Mounting Facility Pattern:

Four position circular

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

1.0 amperes lamp load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

2.00 actuation point pounds per square inch gage and 1.00 deactuation point pounds per square inch gage and 1.00 differential point pounds per square inch gage

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

NSN 5930-00-005-7156

Pressure Switch - Page 2 of 2



Pressure Connector Type:
Gasket seal, threaded internal single connection
Media For Which Designed:
Gas
Style Designator:
Cylindrical
Thread Series Designator:
Unf single pressure connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0