

View Online at <https://aerobasegroup.com/nsn/5930-00-005-8935>

**Hazardous Locations/environmental Protection:**

Driptight

**Overall Length:**

4.062 inches

**Overall Height:**

4.937 inches

**Overall Width:**

2.750 inches

**Body Length:**

3.250 inches

**Longest Horizontal Distance Between Mounting Centers:**

2.500 inches

**Longest Vertical Distance Between Mounting Centers:**

2.125 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Surface

**Thready Qty Per Inch (tpi):**

18 single pressure connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

1000.00 pounds per square inch

**Thread Size:**

0.250 inches single pressure connection

**Mounting Facility Pattern:**

Four position rectangular

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Tab w/screw

**Contact Load Current Rating:**

5.1 amperes resistive load first voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

+0.60/+15.00 actuation point pounds per square inch gage and +0.50/+14.50 deactuation point pounds per square inch gage

**Contact Adjustment Type:**

Internal actuation point serrated nut

**Contact Voltage Rating In Volts:**

460.0 ac at sea level first voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular

**Thread Series Designator:**

Npt single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0