

View Online at <https://aerobasegroup.com/nsn/5930-00-005-8935>

Hazardous Locations/environmental Protection:

Driptight

Overall Length:

4.062 inches

Overall Height:

4.937 inches

Overall Width:

2.750 inches

Body Length:

3.250 inches

Longest Horizontal Distance Between Mounting Centers:

2.500 inches

Longest Vertical Distance Between Mounting Centers:

2.125 inches

Pressure Switch Type:

Gage

Mounting Method:

Surface

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

1000.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Tab w/screw

Contact Load Current Rating:

5.1 amperes resistive load first voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+0.60/+15.00 actuation point pounds per square inch gage and +0.50/+14.50 deactuation point pounds per square inch gage

Contact Adjustment Type:

Internal actuation point serrated nut

Contact Voltage Rating In Volts:

460.0 ac at sea level first voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0