

View Online at <https://aerobasegroup.com/nsn/5930-00-006-3036>

Thread Class:

2a

Body Style:

Hole mount

Hazardous Locations/environmental Protection:

Driptight

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.812 inches

Body Length:

2.789 inches

Body Width:

2.140 inches

Body Height:

1.480 inches

Actuator Style:

Round

Actuator Diameter:

0.430 inches

Actuator Height:

1.080 inches

Actuator Position-action Relationship:

Up position maintained and down position momentary

Actuator Position-locking Relationship:

Up position locked in and down position no locking action

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.138 inches

Nonpile-up Contact Arrangement:

6 pole, single throw, normally closed, momentary action single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

30.000 amperes resistive dc and 20.000 amperes inductive dc and 7.000 amperes lamp dc and 10.000 amperes resistive ac and 7.500 amperes inductive ac

Thread Series Designator:

Unc

Terminal Type And Quantity:

12 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0