

View Online at <https://aerobasegroup.com/nsn/5930-00-006-3036>

**Thread Class:**

2a

**Body Style:**

Hole mount

**Hazardous Locations/environmental Protection:**

Driptight

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.812 inches

**Body Length:**

2.789 inches

**Body Width:**

2.140 inches

**Body Height:**

1.480 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.430 inches

**Actuator Height:**

1.080 inches

**Actuator Position-action Relationship:**

Up position maintained and down position momentary

**Actuator Position-locking Relationship:**

Up position locked in and down position no locking action

**Maximum Voltage Rating In Volts:**

250.0 ac and 30.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.138 inches

**Nonpile-up Contact Arrangement:**

6 pole, single throw, normally closed, momentary action single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

30.000 amperes resistive dc and 20.000 amperes inductive dc and 7.000 amperes lamp dc and 10.000 amperes resistive ac and 7.500 amperes inductive ac

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

12 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0