## NSN 5930-00-006-5430

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-006-5430

### **Thread Class:**

2a single mounting facility

## Thread Length:

0.375 inches single mounting facility

## **Overall Length:**

2.005 inches

#### **Overall Height:**

1.250 inches

#### **Overall Width:**

1.265 inches

#### Shaft Diameter:

0.247 inches single actuator and 0.250 inches single actuator

#### Shaft Length:

0.750 inches single actuator

#### **Nonturn Device Radius:**

## 0.531 inches at 3: 00 o'clock

## Individual Section Quantity:

3

#### Nonturn Device Type:

Tab at 3: 00 o'clock

## Switch Contact Basic Design:

Nonpile-up nonsymmetrical

#### **Mounting Method:**

Threaded bushing single mounting facility

#### **Thread Size:**

0.375 inches single mounting facility

#### **Contact Voltage Rating In Volts:**

28.0 dc at sea level

#### Switch Actuator Indexing Position Quantity:

7 single actuator

#### Shaft Type:

Round single actuator

#### **Terminal Type:**

Tab, solder lug

#### Switch Actuator Positioning Increment:

30.0 degrees single actuator

## Switch Actuator Stop Device Type:

Fixed stop single actuator

## **Contact Load Current Rating:**

500.0 milliamperes resistive load ac at sea level

## Style Designator:

Circular wafer, bushing mount

# NSN 5930-00-006-5430

Rotary Switch - Page 2 of 2



Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A052b0

