NSN 5930-00-007-0678

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-007-0678

Body Style:						
Hole mount						
Hazardous Locations/environmental Protection:						
Corrosion resistant						
Overall Length:						
4.344 inches						
Center To Center Distance Between Mounting Facilities Parallel To Width:						
3.000 inches						
Overall Height:						
7.031 inches						
Overall Width:						
3.812 inches						
Body Length:						
3.219 inches						
Body Width:						
3.812 inches						
Center To Center Distance Between Mounting Facilities Parallel To Height:						
4.500 inches						
Actuator Style:						
Round						
Actuator Height:						
1.125 inches						
Actuator Color:						
Red single actuator						
Maximum Voltage Rating In Volts:						
600.0 ac and 600.0 dc						
End Application:						
Triconderoga class cg or ship, ohio class ssn (trident)						
Inclosure Type:						
Fully enclosed						
Mounting Method:						
Bracket and unthreaded hole						
Features Provided:						
Actuator seal						
Nonpile-up Contact Arrangement:						
1 two circuit, double break/double make, one position momentary single switch unit						
Contact Load Current Rating At Maximum Rated Voltage:						
200.000 milliamperes resistive dc and 1.200 amperes resistive ac						
Precious Material And Location:						
Contacts silver						
Terminal Type And Quantity:						
A service						

4 screw

NSN 5930-00-007-0678

Push Switch - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0