NSN 5930-00-007-0678

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-007-0678

Body Style:

Hole mount

Hazardous Locations/environmental Protection:

Corrosion resistant

Overall Length:

4.344 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches

Overall Height:

7.031 inches

Overall Width:

3.812 inches

Body Length:

3.219 inches

Body Width:

3.812 inches

5.012 1101165

Center To Center Distance Between Mounting Facilities Parallel To Height:

4.500 inches

Actuator Style:

Round

Actuator Height:

1.125 inches

Actuator Color:

Red single actuator

Maximum Voltage Rating In Volts:

600.0 ac and 600.0 dc

End Application:

Triconderoga class cg or ship, ohio class ssn (trident)

Inclosure Type:

Fully enclosed

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Actuator seal

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

200.000 milliamperes resistive dc and 1.200 amperes resistive ac

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

4 screw

NSN 5930-00-007-0678

Push Switch - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0

