

View Online at <https://aerobasegroup.com/nsn/5930-00-007-0714>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.313 inches single mounting facility

**Overall Length:**

8.191 inches

**Overall Height:**

2.063 inches

**Overall Width:**

2.063 inches

**First Flat Length:**

0.250 inches single actuator

**Flat Height:**

0.218 inches single actuator

**Shaft Diameter:**

0.248 inches single actuator and 0.251 inches single actuator

**Shaft Length:**

1.000 inches single actuator

**Nonturn Device Radius:**

0.500 inches at 12: 00 o'clock

**Individual Section Quantity:**

7

**Nonturn Device Type:**

Tab at 12: 00 o'clock

**Operating Temperature Range:**

-65.0 to 125.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section rear

**Throw Quantity:**

12 each section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

300.0 highest ac voltage rating at sea level

**Shaft Flat/slot Angular Location:**

180.0 degrees from contact position 1 single actuator

**Switch Actuator Indexing Position Quantity:**

12 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Detent Rotational Torque Range:**

+1.500 to 10.000 inch-pounds single actuator

**Switch Actuator Stop Device Type:**

Adjustable stop single actuator

**Contact Load Current Rating:**

500.0 milliamperes resistive load dc at sea level and 50.0 milliamperes inductive load dc at sea level

**Style Designator:**

Square wafer, panel mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0