# NSN 5930-00-007-0866

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-007-0866

**Overall Length:** 5.000 inches **Overall Height:** 2.906 inches **Overall Width:** 2.812 inches **Individual Section Quantity:** 3 Knob Manufacturer Code: 82121 **Knob Manufacturer Part Number:** G Longest Horizontal Distance Between Mounting Centers: 2.000 inches single mounting facility **Shortest Horizontal Distance Between Mounting Centers:** 1.000 inches single mounting facility Longest Vertical Distance Between Mounting Centers: 2.188 inches single mounting facility **Operating Tempurature Range:** -65.0 to 125.0 degrees celsius Switch Contact Basic Design: Nonpile-up symmetrical **Pole Quantity:** 1 each section front **Throw Quantity:** 7 each section front **Features Provided:** Actuator knob **Contact Voltage Rating In Volts:** 500.0 highest ac voltage rating at sea level **Mounting Facility Pattern:** Isosceles triangle single mounting facility Switch Actuator Indexing Position Quantity: 8 single actuator **Terminal Type:** Tab w/screw **Contact Switching Action:** Breaks before makes each section front **Switch Actuator Positioning Increment:** 45.0 degrees single actuator Switch Actuator Stop Device Type: Adjustable stop single actuator

# NSN 5930-00-007-0866

Rotary Switch - Page 2 of 2



### **Contact Load Current Rating:**

5.0 amperes resistive load highest ac voltage rating at sea level

#### Style Designator:

Tap, circuit selector

### Test Data Document:

81349-mil-s-18396 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A052b0