

View Online at <https://aerobasegroup.com/nsn/5930-00-007-3937>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

6.219 inches

**Overall Height:**

1.656 inches

**Overall Width:**

2.593 inches

**Unthreaded Mounting Hole Diameter:**

0.203 inches

**Actuator Length:**

Between 1.625 inches and 3.625 inches

**Actuator Style:**

Roller arm

**Actuator Roller Diameter:**

0.750 inches

**Actuator Roller Width:**

0.281 inches

**Housing Height:**

1.656 inches

**Housing Length:**

2.844 inches

**Housing Width:**

1.781 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Height:**

1.156 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Length:**

2.344 inches

**Maximum Voltage Rating In Volts:**

440.0 ac and 230.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Features Provided:**

Actuator seal

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Actuating Force:**

32.0 ounces

**Actuator Movement:**

10.0 pretravel degrees and 50.0 overtravel degrees and 4.0 differential degrees

**Contact Load Current Rating At Maximum Rated Voltage:**

200.000 milliamperes resistive dc and 6.000 amperes resistive ac

**Special Features:**

Two 0.203 in. Diameter mtg holes diagonally spaced on 2.344 in. By 1.156 in. Mtg centers

**Terminal Type And Quantity:**

3 tab w/screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0