

View Online at <https://aerobasegroup.com/nsn/5930-00-007-3990>

Thread Class:

2b

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Actuator Length:

1.000 inches

Actuator Style:

Roller arm

Actuator Free Position Height:

0.562 inches

Actuator Roller Width:

0.109 inches

Actuator Adapter Style:

Roller arm

Housing Length:

0.779 inches

Housing Width:

0.250 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Height:

0.391 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

0.375 inches

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded hole

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

56

Thread Size:

0.086 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

60.0 ounces

Actuator Movement:

0.125 pretravel inches and 0.030 overtravel inches and 0.030 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac

Thread Series Designator:

Unc

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0