

View Online at <https://aerobasegroup.com/nsn/5930-00-007-7628>

Thread Class:

2a single mounting facility

Thread Length:

0.343 inches single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

2.367 inches

Shaft Diameter:

0.123 inches single actuator and 0.127 inches single actuator

Shaft Length:

0.750 inches single actuator

Overall Diameter:

0.750 inches

Individual Section Quantity:

4

Nonturn Device Type:

Flatted bushing at 3: 00 o'clock

Operating Temperature Range:

-62.0 to 85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

12 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Rotor Through Connection Quantity:

1 each section

Switch Actuator Indexing Position Quantity:

12 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

250.0 milliamperes resistive load and 125.0 milliamperes inductive load dc at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0