NSN 5930-00-007-7666

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-007-7666	
Thread Class:	
3a single pressure connection	
Hazardous Locations/environmental Protection:	
Fungus proof	
Overall Length:	
3.000 inches	
Outside Diameter:	
0.438 inches single connection	
Body Length:	
2.450 inches	
Overall Diameter:	
0.900 inches	
Pressure Switch Type:	
Gage	
Width Across Flats:	
0.750 inches	
Operating Tempurature Rating:	
Between -65.0 degrees fahrenheit and 275.0 degrees fahrenheit	
Mounting Method:	
Inlet connection	
Features Provided:	
Hermetically sealed case	
Contact Action Stimulus:	
Increase	
Proof Pressure:	
2250.00 pounds per square inch	
Thread Size:	
0.438 inches single pressure connection	
Nonpile-up Contact Arrangement:	
1 pole, double throw, one position momentary	
Sensing Element Burst Pressure:	

3750.00 pounds per square inch

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

5.0 amperes resistive load single voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

400.00 actuation point pounds per square inch and 300.00 deactuation point pounds per square inch

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

NSN 5930-00-007-7666

Pressure Switch - Page 2 of 2



Pressure Connector Type:
Flared, threaded external single connection
Media For Which Designed:
Liquid
Style Designator:
Cylindrical
Thread Series Designator:
Unjf single pressure connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0