

View Online at <https://aerobasegroup.com/nsn/5930-00-007-8700>

Thread Length:

0.230 inches and 0.255 inches single mounting facility

Hazardous Locations/environmental Protection:

Dustproof

First Flat Length:

0.235 inches and 0.265 inches single actuator

Flat Height:

0.093 inches single actuator

Shaft Diameter:

0.123 inches and 0.126 inches single actuator

Shaft Length:

0.605 inches and 0.645 inches single actuator

Overall Diameter:

Between 0.547 inches and 0.577 inches

Individual Section Quantity:

1

Operating Temperature Range:

-65.0 to 85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

12 single section rear

Mounting Method:

Threaded bushing w/panel seal single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

280.0 degrees from contact position 1 single actuator

Switch Actuator Indexing Position Quantity:

12 single actuator

Shaft Type:

Round, flatted single actuator

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Detent Rotational Torque Range:

+0.500/+1.500 inch-pounds single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

200.0 milliamperes resistive load dc at sea level

Style Designator:

Miniature, bushing mount

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0