

View Online at <https://aerobasegroup.com/nsn/5930-00-007-8701>

Thread Length:

0.292 inches and 0.332 inches single mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

2.005 inches

First Flat Length:

0.230 inches and 0.270 inches single actuator

Flat Height:

0.084 inches and 0.104 inches single actuator

Shaft Diameter:

0.123 inches and 0.126 inches single actuator

Shaft Length:

0.647 inches and 0.727 inches single actuator

Overall Diameter:

0.765 inches

Nonturn Device Radius:

0.260 inches at 1:00 o'clock

Individual Section Quantity:

2

Nonturn Device Type:

Pin at 1:00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section rear

Throw Quantity:

12 each section rear

Mounting Method:

Threaded bushing w/panel seal single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

30.0 dc at sea level

Shaft Flat/slot Angular Location:

280.0 degrees from contact position 1 single actuator

Switch Actuator Indexing Position Quantity:

12 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Detent Rotational Torque Range:

+5.000 to 32.000 inch-ounces single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

125.0 milliamperes resistive load dc at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0