

View Online at <https://aerobasegroup.com/nsn/5930-00-007-9269>

Thread Class:

2a single mounting facility

Thread Length:

0.312 inches single mounting facility

Overall Length:

3.828 inches

Overall Height:

1.828 inches

Overall Width:

1.609 inches

Shaft Diameter:

0.266 inches 1st actuator and 0.268 inches 1st actuator

Shaft Length:

0.906 inches 2nd actuator

Nonturn Device Radius:

0.531 inches at 3:00 o'clock

Individual Section Quantity:

4

Nonturn Device Type:

Pin at 3:00 o'clock

Operating Temperature Range:

-65.0 to 125.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

13 1st actuator

Shaft Type:

Round, slotted 1st actuator

Terminal Type:

Tab, solder lug

Switch Actuator Positioning Increment:

30.0 degrees 2nd actuator

Detent Rotational Torque Range:

+2.000 to 2.500 inch-pounds 1st actuator

Switch Actuator Stop Device Type:

Fixed stop all actuators

Contact Load Current Rating:

200.0 milliamperes resistive load dc at sea level and 20.0 milliamperes inductive load dc at sea level

Style Designator:

Tap, square frame

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0